



Gimmie The White Stuff™



Gimmie the White Stuff®



Description

All purpose **PTFE THREAD SEALING COMPOUND** that produces leakproof seals on threaded connections. Lubricates, seals and protects threads in an extensive variety of plumbing, heating and oil field threaded pipe connections over a wide range of services, temperatures and pressures. Will not dry out, stain, harden or separate. Non-toxic. Will not destroy the seals of valves or faucets. Wipes clean from hands easily.

Characteristics

Jomar Seal PTFE, soft-set thread sealing compound is recommended for residential and commercial applications where cleanliness is essential. Non-seizing breaks out easily without stripping, galling or damaging threads. Free of halogens. Not affected by oils, dilute caustics or dilute acids.

Recommended For Use On

- Acids, dilute
- Air, compresses gaseous
- Ammonia
- Aliphatic Solvents
- Brine
- Carbon Dioxide
- Caster Oils
- Caustic Alkali, dilute
- Diesel Fuel Oil
- Freons (all)
- Gasoline
- Heating Oils
- Helium, Gaseous
- Hydraulic oils
- Inert Gasses
- Jet Fuel (JP4,5,6)
- Kerosene
- Liquified Petroleum
- Manufactured Gases
- Mineral Oils
- Natural Gases
- Nitrogen, Gaseous
- Petroleum Solvents
- Steam
- Sugar, Liquid
- Water, Potable, hot or cold

NOT FOR USE ON OXYGEN

Warranty

The Company, for a period of one year from the date of shipment, warrants each product or system of its own manufacture to the original purchaser to be free from defects in material and workmanship under normal use, service and maintenance.

Directions

Stir before using. Clean oil, dirt, grease or any foreign material from threads. Apply only to male threads. Use on all metal, plastic, PVC or, Fiberglass, CPVC, and NYLON threads.

CONTAINS NO LEAD

Temperature/Pressure Ranges

Temperature Ranges: -50°F to +400°F;
Flash Point 43°F
Brushable to -50°F

Pressure Ranges: Gases to 3,000 PSI
Liquids to 8,000 PSI

MAY BE LEFT ON TRUCK OVERNIGHT IN WINTER WEATHER AND CAN BE BRUSHED WHEN PRODUCT IS EXPOSED TO BELOW 0°F TEMPERATURES WITH NO SEPARATION.

Architect/Engineer approval

Job Name _____ Date _____
 Model Specified _____ Quantity _____
 Variations Specified _____
 Customer/Wholesaler _____
 Contractor _____
 Architect _____

Note: Information subject to change without notice.



Jomar International Ltd.
 7243 Miller Drive
 Warren, MI 48092
 Phone: 800-325-5690
 Fax: 800-628-4194
 www.jomar.com

